

# CONSTRUCTION Lubricants



*Trent's range of Construction Products are designed to exceed the standards and provide the end user with a confidence that only comes from using a top quality product*



# CONSTRUCTION Lubricants

## Trent Bio Mould 35

### RANGE ISO VG; 4

Low viscosity VOC Free concrete release agent/mould oil formulated from a single base oil and a suitable additive system ideal for effective concrete release, providing optimum concrete release for various process' including the manufacture of fence post, piles and thin flat sections. Trent Bio Mould 35 is recommended for use with plastic moulds and is particularly suitable for situations where an excellent finish is desired. This product is inherently Bio degradable.

## Trent BIO Hydraulic Oil

### RANGE ISO ISO VG; 32,46

Manufactured from vegetable base oil whilst using a carefully selected and balanced combination of ash-free anti-wear, anti-corrosion, anti-oxidant and anti-foam additives.

### BENEFITS

- Biodegradable
- Ashless technology
- Suitable for environmental applications where losses may occur.
- Good anti-wear performance
- Good oxidation stability.
- Good corrosion protection.

## Trent Lithium EP 2

### NLGI: 2

Lithium based high melting point (EP) extreme pressure grease. General purpose grease suitable for all anti-friction and plain bearings subjected to high load conditions. Used extensively for applications throughout industry and the automotive sector.

## Trent Lithium EPM

### NLGI: 2

Lithium EPM is a Premium quality multi-purpose grease for lubricating all anti-friction and plain bearings subjected to high load conditions. The incorporation of molybdenum disulphide imparts a high degree of wear protection against load shock loading and dusty environments.

## Trent Lithium EP 00

### NLGI: 00

Lithium EP 00 is a Premium quality semi-fluid grease designed for centralised lubrication systems. Suitable for anti-friction and plain bearings subjected to high load condition also suitable for gearboxes designed to operate with a semi-fluid slumping grease.

## Trent Bio Mould BC

### RANGE ISO VG; 12

Low viscosity concrete release agent/mould oil formulated from a single base oil and a suitable additive system ideal for effective concrete release.

Trent Bio Mould BC provides optimum concrete release for various process' including the manufacture of fence post, piles and thin flat sections.

This product is inherently Bio degradable.

## Trent Industrial Gear Oil

### RANGE ISO VG; 32,68,100,150, 220, 320, 460, 680

Specially designed for the lubrication of enclosed gears, Industrial worm, helical and various other speed reducing fixed ratio gearboxes which require EP (extreme pressure) lubricants. Produced using the highest quality solvent refined base stocks, high levels of anti-wear, anti-foam properties combined with extreme pressure (EP) additives.

### MEETS THE FOLLOWING SPECIFICATIONS

- US Steel 224
- AGMA 250.04
- MIL-L-2105
- Excellent extreme-pressure and anti-wear properties
- Good product stability at operating temperatures.
- Good anti-corrosion properties
- Non-staining to yellow metals
- Excellent Gear protection
- Not compatible with oils based on polyglycol

## Trent Lithium Complex EP 2

### NLGI: 2

Red in appearance this is a premium quality multi-purpose lithium complex grease for lubricating all anti-friction and plain bearings for use in industrial and automotive applications. This highly adhesive grease has shown exceptional performance providing extended lubrication intervals, even under arduous conditions and over wide operating temperature range.

## Trent Lithium EP 0

### NLGI: 0

Lithium EP 0 is a premium quality multi-purpose semi fluid grease for use in all anti-friction and plain bearings subjected to high load conditions. The incorporation of extreme pressure and anti-wear additives imparts a high degree of wear protection against load. Used extensively for applications throughout industry and the automotive sector.

## Trent Lithium EP 000

### NLGI: 000

Lithium EP 000 is a Premium quality multi-purpose semi fluid grease for use in all anti-friction and plain bearings subjected to high load conditions. The incorporation of extreme pressure and anti-wear additives imparts a high degree of wear protection against load. Used extensively for applications throughout industry and the automotive sector.

## Trent Mould H

### RANGE ISO VG; 32

A medium viscosity concrete release agent/mould oil formulated from a single base oil and a suitable additive system ideal for effective concrete release. Trent Mould H provides optimum concrete release for various process' including the manufacture of fence post, piles and thin flat sections.

Pronounced benefits when used with plastic moulds where previous splitting has been experienced also offering clean concrete surface after release.

## Trent Turbofleet 15w40

Trent Turbofleet 15w-40 is a Super High Performance Diesel Engine Lubricant designed for the low emission Euro IV & Euro V engines. May also be used in passenger cars with both petrol and diesel engines

### SPECIFICATIONS

- ACEA E7/ E5/ E3/ B4/ B3/ A3
- API SL/CI-4

### MEETS THE FOLLOWING SPECIFICATIONS

- MB 228.3
- MAN M3275
- Deutz DQC 11-05
- VOLVO VDS-3
- MTU Type 2
- Renault VI RLD & RLD-2
- Cummins CES 20071, -72, -76, -77, -78
- Caterpillar ECF-1 & ECF-2



TRENT  
LUBRICANTS

Lubricating Solutions since 1971

Trent Oil Lubricants Limited | Phoenix House | Kemmel Road | Bulwell | Nottingham NG6 9FH | T: 0845 270 1122 | F: 0115 927 9982  
E: sales@trentoil.co.uk | www.trentoil.co.uk

