

Trent Bio Chain Oil 36

Biodegradable Chain Saw Oil

Description

Trent Bio Chain Oil 36 is manufactured using a naturally derived ester containing vegetable oils whilst utilising specially selected additives.

Special care and attention has been taken to identify the perfect combination of additives to fulfil our customers ever demanding expectations.

Application

Trent Chain Saw Oil is recommended for the lubrication of chains where the prevention of stick, slip and chatter is required.

Benefits

- Biodegradable.
- Ashless technology.
- EP performance.
- Excellent anti-stick-slip properties
- Suitable for environmental applications where losses may occur.
- Strong stickiness.
- Good anti-wear performance.
- Good oxidation stability.
- Good corrosion protection.

Typical Inspection Data

Property	Method	Units	Inspection Data
Viscosity Grades	-	-	32 - 46
Flash Point	D 92	°C	200
Specific Gravity @ 15.6°C		kg/m3	0.922

Health and Safety

Please refer to the relevant Trent Safety Data Sheet.

January 2017

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT. Trent Oil Lubricants Ltd. assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of Trent Oil Lubricants Ltd.



Trent Oil (Lubricants) Limited,

Phoenix House, Kemmel Road, Bulwell, Nottingham, England NG6 9FH

Tel: 0115 9279 166, Fax: 0115 9279 982

technical data