

Trent Chain Saw Oil Heavy

Description

Trent Chain Saw Oil Heavy is manufactured from the highest quality solvent refined base stocks and a special fourfold additive package.

Application

Trent Chain Saw Oil Heavy is recommended for the lubrication of chains where the prevention of stick, slip and chatter is required.

Performance Profile

- Excellent extreme-pressure properties.
- Excellent anti-stick-slip properties promoting smooth table operation.
- Strong stickiness.
- Very low coefficient of friction.
- Anti-Oil mist properties.
- Outstanding anti-wear and anti-corrosion properties.

Typical Inspection Data

Property	Method	Units	Inspection Data
Viscosity Grade	-	-	220
Viscosity at 40°C	D 445	mm ² /s	220
Viscosity at 100°C	D 445	mm ² /s	19
Flash Point	D 92	°C	>200
Viscosity Index	D 2270	-	104
Specific Gravity @ 15.6°C		kg/m ³	0.896

Health and Safety

Please refer to the relevant Trent Safety Data Sheet.

January 2017

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT. Trent Oil Lubricants Ltd. assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of Trent Oil Lubricants Ltd.



Trent Oil (Lubricants) Limited,

Phoenix House, Kemmel Road, Bulwell, Nottingham, England NG6 9FH

Tel: 0115 9279 166, Fax: 0115 9279 982

technical data