

Trent Microturn SCL 410

Neat Cutting Oil

Description

Trent Microturn SCL 410 is a pale, low odour, chlorinated neat cutting oil containing extreme pressure, anti-wear and lubricity additives blended in carefully selected mineral base oils.

Application

Trent Microturn SCL 410 is a multi-metal high performance neat cutting oil, with low viscosity characteristics, for use on high tensile steels, stainless steel and alloys.

Trent Microturn SCL 410 has been specifically designed for use on sliding head CNC and multi-spindle machines and is also suitable for broaching and gear manufacturing.

Application Selector Chart

	Turning	Drilling	Milling	Honing	Threading	Deep Hole Drilling
Steel	●	●	●	●	●	●
Stainless Steel	●	●	●	●	●	●
High Alloy Steel	●	●	●	●	●	●
Titanium	●	●	●	●	●	●
Copper Alloys	●	●	●	●	●	●
Through Tool	●	●	●	●	●	●

●	Excellent	○	Acceptable	–	Not Suitable
---	-----------	---	------------	---	--------------

Benefits

- High Quality Mineral Oil.
- Low Aromatic Content.
- Low Viscosity.
- High Lubricity, EP and Anti-wear Performance.
- Prolonged tool life due to anti-wear technology.
- Excellent Surface Finish.

Typical Inspection Data

Property	Method	Units	Inspection Data
Viscosity Grade	-	-	10
Viscosity at 40°C	D 445	mm ² /s	10.52
Flash Point	D 93	°C	130
Sulphur			Inactive
Chlorine			Yes
Anti-Friction			Yes

Health and Safety

Please refer to the relevant Trent Safety Data Sheet.

January 2017

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT. Trent Oil Lubricants Ltd. assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of Trent Oil Lubricants Ltd.



Trent Oil (Lubricants) Limited,

Phoenix House, Kemmel Road, Bulwell, Nottingham, England NG6 9FH

Tel: 01159 279 166, Fax: 0115 9279 982

technical data