Trent Brick 35

Concrete Release Agent

technical data

Description

Trent Brick 35 is a low viscosity general purpose mould release and extrusion oil, formulated using a highly refined mineral oil and solvent to promote fast drying, **not** suitable for plastic moulds.

Application

Trent Brick 35 is to be applied by spray, brush or swab.

Benefits

- Good surface finish.
- Pale colour.
- Non-staining.
- Fast drying.

Typical Inspection Data

Property	***Method***	***Units***	***Inspection Data***
Viscosity Grade	-	-	2.5
Viscosity at 40°C	D 445	mm^2/s	2.44
Absolute Density, 15°C	D 4052	g/ml	0.812
Flash Point	D 92	°C	75

Health and Safety

Please refer to the relevant Trent Safety Data Sheet.

January 2017

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT. Trent Oil Lubricants Ltd. assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of Trent Oil Lubricants Ltd.

TRENT LUBRICANTS

Trent Oil (Lubricants) Limited,
Phoenix House, Kemmel Road, Bulwell, Nottingham, England NG6 9FH

Tel: 01159 279 166, Fax: 0115 9279 982