

Trent Mould 36

Concrete Release Agent

Description

Trent Mould 36 is a low viscosity mould oil formulated from a single base oil system ideal for effective concrete release.

Application

Trent Mould 36 can be safely used with various mould types and is particularly suitable for situations where an excellent finish is desired.

Benefits

- Low viscosity oil which can be applied by brush or spraying with minimum oil mist formation.
- Pronounced benefits when used with plastic moulds where previous splitting has been experienced.

Typical Inspection Data

Property	Method	Units	Inspection Data
Viscosity Grade	-	-	16
Viscosity at 40°C	D 445	mm ² /s	15.86
Absolute Density, 15°C	D 4052	g/ml	0.854
Flash Point	D 92	°C	130

Health and Safety

Please refer to the relevant Trent Safety Data Sheet.

January 2017

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT. Trent Oil Lubricants Ltd. assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of Trent Oil Lubricants Ltd.



Trent Oil (Lubricants) Limited,
Phoenix House, Kemmel Road, Bulwell, Nottingham, England NG6 9FH

Tel: 01159 279 166, Fax: 0115 9279 982

technical data