Trent ATF Dexron III

Semi Synthetic Automatic Transmission Fluid.

Description

Trent ATF Dexron III is a multi-purpose automatic transmission fluid for commercial and passenger car gearboxes meeting a very wide range of specifications. The automatic transmission is one of the most complicated mechanisms in modern automotive engineering and consequently requires complex fluids for efficient operation.

Trent ATF Dexron III is manufactured from premium synthetic base stocks and high-quality solvent refined base oils with specially selected additives and friction modifiers to produce a lubricant with outstanding durability. It demonstrates excellent frictional stability and offers extended fluid life even when under the most severe conditions.

Application

Trent ATF Dexron III is recommended for automatic transmissions and power steering units in cars, vans, trucks, buses, agricultural and industrial machines where the following specifications are required.

Product Specification:

General Motors
Dexron IIIH, Dexron IIIG, Dexron IID, TASA

Ford Mercon
Allison C-4, TES-389

Mercedes Benz
236.10, 236.9, 236.8, 236.7, 236.6, 236.5, 236.1

Caterpillar TO-2

MAN
339F, 339 V1 & Z1, 339 V2 & Z2

Voith 55.6335 (G607)
Volvo 97341, 97340

TE-ML 02F, 03D, 04D, 09, 11A, 11B, 14A,14B, 16L 17C

Benefits

- Long oil life
- Improves clutch durability
- Can be used as a power steering fluid
- Excellent protection against wear
- Low foaming tendencies
- Compatible with all elastomers and other sealing materials
- High thermal stability

Typical Inspection Data

Property	
Appearance	Red
Density at 15.6°C	0.882
Viscosity at 100°C	7.91
Flash Point COC (°C)	205

Health and Safety

Please refer to the relevant Trent Safety Data Sheet.

June 2019

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT. Trent Oil Lubricants Ltd. assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of Trent Oil Lubricants Ltd.



Trent Oil (Lubricants) Limited,

Phoenix House, Kemmel Road, Bulwell, Nottingham, England NG6 9FH

Tel: 01159 279 166, Fax: 0115 9279 982



