

Trent Microcore M12

Medium Term Indoor Rust Preventative

Description

Trent Microcore M12 is a light bodied solvent deposited oily film, temporary corrosion preventative, suitable for Ferrous components, to give medium term inter-operational protection.

Trent Microcore M12 is designed to offer inter-operational protection when applied correctly to Ferrous components. This product is manufactured using hydrocarbon distillate and contains highly refined mineral oil of low aromatic content and specially selected corrosion inhibitors.

Trent Microcore M12 will provide up to 12 months protection of parts (indoors) depending on storage conditions.

Application

Application can be made by brush, cold dip or spray.

The film is thin clear and oily, this can be removed if required by using an Alkaline Cleaner, Hydrocarbon Solvents or Vapour De-greaser.

Benefits

- Medium-term indoor protection with a very light economical thin film.
- Contains specially selected corrosion inhibitors.
- Economical high surface coverage.

Typical Inspection Data

Property	Inspection Data
Appearance	Clear Brown Fluid / Slightly Hazy
Density at 15°C	0.820
Film Type	Thin, Clear, Oily and Non Hardening

Health and Safety

Please refer to the relevant Trent Safety Data Sheet.

January 2017

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT. Trent Oil Lubricants Ltd. assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of Trent Oil Lubricants Ltd.



Trent Oil (Lubricants) Limited,

Phoenix House, Kemmel Road, Bulwell, Nottingham, England NG6 9FH

Tel: 01159 279 166, Fax: 0115 9279 982

technical data