

SUTO 15W-30

Mineral oil based super universal tractor oil.

Description:

Trent SUTO 15w-30 is a Super Universal Tractor Oil grade suitable for engines, transmissions, hydraulics and final drives.

The latest agricultural machinery in the modern intensive farming environment needs the protection of a high quality lubricant.

Trent SUTO 15w-30 is blended from carefully selected base oils and the latest in additive technology to produce a lubricant for the demands of most farm equipment. The latest additives used help reduce wet brake noise. The carefully selected base oils ensure protection even under the most arduous of conditions.

Application:

Trent SUTO 15w-30 is suitable for use in both normally aspirated and turbocharged diesel and petrol engines, transmission systems including those fitted with wet brakes, hydraulic systems, oil immersed clutches, gearboxes and final drives. It is suitable for agricultural, plant and off road machinery.

Product Specifications:

- | | | | |
|-----------|------------------------------|-------------------|--------------------------|
| • API | CE/SF (Engine), GL-4 (Gears) | • Massey Ferguson | 1135, 1127, 1139 |
| • CCMC | D4/G2 | • John Deere | J20A |
| • MB | 227.1 | • Caterpillar | TO-2 |
| • Allison | C4 | • ZF | TE ML 06B, 06L, 07B, 07D |
| • Ford | M2C 86A, 134B/C, 159B | | |

Benefits:

- Suitable for many agricultural machinery.
- Helps reduce wet brake noise or “squawk”.
- Meets a variety of OEM requirements.
- API diesel & petrol engine

Typical Inspection Data

Property	Method	Units	Inspection Data
Density at 15.6°C	D1298	kg/m ³	0.883
Viscosity at 100°C	D 445	mm ² /s	11.49
Viscosity at 40°C	D 445	mm ² /s	85.04
Viscosity Index	D 2270	-	125
Flash Point	D 92	°C	218
Pour Point	D 97	°C	-31
TBN (mg KOH/g)	D2896	mg KOH/g	10.38

Health and Safety

Please refer to the relevant Trent Material Safety Data Sheet.

Oct 2018

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT. Trent Oil Lubricants Ltd. assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of Trent Oil Lubricants Ltd.



Trent Oil (Lubricants) Limited,

Phoenix House, Kemmel Road, Bulwell, Nottingham, England NG6 9FH

Tel: 01159 279 166, Fax: 0115 9279 982

technical data