

TRENT TFR 20

Heavy Duty Traffic Film Remover

Description

Trent TFR 20 is a carefully formulated combination of surface active agents, sequestrants, alkaline builders and solvents which work quickly and effectively to remove traffic film, dirt, grease and soiling.

Trent TFR 20 may be applied in a number of ways and under varying dilution rates dependent upon conditions. This allows the user to achieve perfect cleaning of heavily soiled vehicles with the minimum of effort. Although predominantly marketed as a TFR this product is also suitable as a floor cleaner and is particularly effective at cleaning garage forecourt areas.

Application

Trent TFR 20, whilst a heavy- duty alkaline based solution is safe when diluted as recommended. This product, when used as recommended will not affect paint, rubber, wiring or glass. Typical users are haulage companies, commercial fleet owners, industrial delivery vehicles, coach and bus operators, quarry, coal, milk, oil, farming, plant hire etc. Particularly recommended for vehicle and plant cleaning. Although predominantly marketed as a TFR this product is also suitable as a floor cleaner and is particularly effective at cleaning garage forecourt areas.

Dilution

Trent TFR 20 may be applied to the vehicle by spray, brush, sponge, mop or powerwash equipment. The product may be used at a dilution rate of between 1:50 and 1:300 with hot or cold water depending upon method of application and degree of soiling. The vehicle should be hosed down with water after cleaning and allowed to dry.

As a floor cleaner recommended dilutions are between 5 and 50 :1 depending on the severity of the soiling. (the product can be applied neat for spot treatment if required)

Typical Inspection Data

Property	Method	Units	Inspection Data
Appearance	-	-	Clear Liquid
Colour	-	-	Green
Specific Gravity @ 20°C	-	kg/m ³	1.04 – 1.07
pH of Neat Product	-	-	14

Health and Safety

Please refer to the relevant Trent Safety Data Sheet.

October 2023

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT. Trent Oil Lubricants Ltd. assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of Trent Oil Lubricants Ltd.



Trent Oil (Lubricants) Limited,

Phoenix House, Kemmel Road, Bulwell, Nottingham, England NG6 9FH

Tel: 0115 927 9166, Fax: 0115 9279 982

technical data