

Trent Vanishing Lube Light

Vanishing Type Metalforming Lubricant

Description

Trent Vanishing Lube Light is a specially formulated conventional `vanishing` type lubricant for light duty metalforming applications where minimal residual lubricant film is required on the finished component.

Trent Vanishing Lube Light is manufactured using low odour materials and is pleasant in use, this product is also completely free from Chlorine & Sulphur.

Application

Trent Vanishing Lube Light has been created for use in light duty presswork and stamping operations of both ferrous and non-ferrous alloys.

Recommendations for use

Trent Vanishing Lube Light is to be used neat as supplied. This product can be applied by dipping, spray, brush or roller.

Benefits

- Low odour hydrocarbon base.
- Suitable for ferrous and non-ferrous materials.
- Very clean evaporative properties..
- No added chlorine or sulphur.
- Minimal residual film left on components.

Typical Inspection Data

Property	Method	Units	Inspection Data
Viscosity at 40°C	D 445	mm ² /s	1.5
Specific Gravity at 15.5°C		kg/m ³	0.801
Flash Point (open)	D 92	°C	>70
Odour		-	Light Paraffinic
Appearance	-	-	Clear Colourless liquid
Water Solubility	-	-	Insoluble

Health and Safety

Please refer to the relevant Trent Safety Data Sheet.

January 2017

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT. Trent Oil Lubricants Ltd. assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of Trent Oil Lubricants Ltd.



Trent Oil (Lubricants) Limited,

Phoenix House, Kemmel Road, Bulwell, Nottingham, England NG6 9FH

Tel: 01159 279 166, Fax: 0115 9279 982

technical data