Trent Compressor Oil UN 150

Rotary & Reciprocating Air Compressor Lubricant

technical data

Description

Trent Compressor Oil UN 150 is manufactured from the highest quality solvent refined base stocks with a multi-functional high performance additive system.

Application

Trent Compressor Oil UN 150 is to be used as received and recommended for the lubrication of rotary and reciprocating compressors. This product may also be used as a vacuum pump oil in accordance to the equipment manufacturers requirements and specifications.

Trent Compressor Oil UN 150 should be used in conditions where the discharge temperature does not exceed 100°C, otherwise the use of a synthetic grade is recommended.

Performance Profile

- DIN 51506 (VBL, VCL, VDL)
- High levels of oxidation resistance for enhanced protection.
- Effective corrosion protection, ferrous and non ferrous.
- Resists emulsification and filter blocking.
- Outstanding anti-wear and anti-corrosion properties.

Typical Inspection Data

Property	***Method***	***Units***	***Inspection Data***
Viscosity Grade	-	-	150
Viscosity at 40°C	D 445	mm^2/s	143
Viscosity at 100°C	D 445	mm^2/s	14.2
Flash Point	D 92	°C	>200
Viscosity Index	D 2270	-	96
Specific Gravity @ 15.6°C		kg/m^3	0.892

Health and Safety

Please refer to the relevant Trent Safety Data Sheet.

January 2017

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT. Trent Oil Lubricants Ltd. assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of Trent Oil Lubricants Ltd.

TRENT LUBRICANTS

Trent Oil (Lubricants) Limited,
98A Lilac Grove, Beeston, Nottingham, NG9 1PF

Tel: 01159 279 166, Fax: 0115 9279 982