Trent Cool 8800 CU

Water Soluble Formaldehyde Release Biocide Free Metalworking Fluid

Technical data

Description

Trent Cool 8800 CU is a high-performance Formaldehyde release biocide free, semi synthetic water-soluble metal working fluid designed for various machining applications offering superb emulsion stability.

Trent Cool 8800 CU is a medium oil content product created using chlorine free lubricity additives which assist in offering excellent cutting performance and a superior surface finish.

Application

Trent Cool 8800 CU is low foaming in use and can be used on through spindle coolant systems. It is suitable for use on a variety of steel alloys and can be used for the machining of non-ferrous alloys.

Trent Cool 8800 CU is an extremely robust soluble metal working fluid providing extended service life in the most difficult conditions.

Benefits

- Very long sump life — Extends intervals between system cleanouts.
- Ultra-low foam — Ideal for the highest working speeds and pressures.
- Exceptional tool performance — Advanced technology minimizes tool wear & tool costs
- Operator Friendly — Outstanding tramp oil rejection properties.
- Superior lubricity — Ideal for continuous operation

Typical Inspection Data

Properties	Inspection Data
Appearance/ Colour	Amber Liquid
Emulsion Type	Semi-Translucent Emulsion
pH Diluted @ 5%	0.93 typical
Foaming tendency @ 5% in 50ppm water	Nil foam after 5 seconds
IP 287 Corrosion Break Point, % Volume:	2.0
Refractometer Factor	1.0
Reichert lubricity at 10% dilution; Noise Reduction (metres)	2.6

Concentration Range

4-10% depending on type of operation.

Mixing

Use coolant mixing valves where possible. When mixing by hand slowly add concentrate to water whilst stirring vigorously. Coolants should not be mixed in the machine sump and avoid using chilled water.

Top Up

Coolant concentration may increase in use due to water evaporation. To maintain the recommended concentration, top up should be made with a more dilute concentration and not by water alone.

TRENT LUBRICANTS

Trent Oil (Lubricants) Limited,
98A Lilac Grove, Beeston, Nottingham, NG9 1PF

Tel: 01159 279 166, Fax: 0115 9279 982

Trent Cool 8800 CU

Water Soluble Formaldehyde Release Biocide Free Metalworking Fluid

OPERATIONS	DILUTION	
Turning	5-7 %	●
Milling	5-7 %	●
Drilling	5-7 %	●
Surface & Cylindrical Grinding	3-4 %	●
Tapping-Threading	7-10 %	●

MATERIALS	
Steel	●
Stainless Steel	●
High Alloy Steel	●
Aluminium Alloys	●
Copper Alloys	●

● Main Application

Fluid Maintenance

Poor or incorrect emulsion preparation may lead to instability and could considerably shorten the life of the emulsion. Prior to making any fresh fill, we would highly recommend full cleaning including the use of a compatible system cleaner.

Water Quality

Coolant performance can be affected by extremes of water quality. Hard water (in excess of 300 ppm CaCO3) and high levels of chlorides and sulphates can reduce the stability of emulsions and reduce corrosion protection. Please contact your Trent Lubricants area manager and they will gladly advise on local water quality.

Contamination

Where possible avoid contamination from foreign matter and other fluids. Remove swarf and tramp oil from the machine sumps frequently.

Disposal

Discarded metal working coolants may be removed by a competent waste contractor. Alternatively, the product may be treated by conventional oil separation and effluent disposal methods. Specific advice is available on request. Product concentrate or diluted fluid should not be introduced into waterways. It is advisable to consult the Local Water Authority regarding disposal.

Storage

Metal working coolants should be stored indoors in clean, dry conditions.
Protect from frost as the recommended storage temperature with all metal working products is between 4°C and 35°C. A shelf life of six months can be anticipated.

Health and Safety

Please refer to the relevant Trent Safety Data Sheet.

May 2024

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT. Trent Oil Lubricants Ltd. assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of Trent Oil Lubricants Ltd.

technical data

TRENT LUBRICANTS

Trent Oil (Lubricants) Limited,
98A Lilac Grove, Beeston, Nottingham, NG9 1PF

Tel: 01159 279 166, Fax: 0115 9279 982