Trent Microcore Q6

Short Term Indoor Rust Preventative

Description

Trent Microcore Q6 is a light bodied solvent deposited oily film, temporary corrosion preventative suitable for Ferrous components, to give short term inter-operational protection.

Trent Microcore Q6 is designed to offer inter-operational protection when applied correctly to Ferrous components.
Trent Microcore Q6 will provide up to 6 months protection of parts (indoors) and up to 3 months (outdoors) depending on storage conditions.

Application

Trent Microcore Q6 should be used as received and may be applied by brush, dip, or spray application at room temperature.
Where water displacement is of primary importance, the dip tank should be equipped with a bottom drain for removing accumulated water.
The film is thin clear and oily, this can be removed if required by using an Alkaline Cleaner, Hydrocarbon Solvents or Vapour De-greaser.

Benefits

- Low odour
- Contains specially selected corrosion inhibitors.
- Good Water displacement.
- Non staining.
- Easily removable film.

Typical Inspection Data

Property	***Inspection Data***
Appearance	Amber Fluid
Density at 15°C	0.83
Salt Spray Performance ASTM B117 (avg. hours)	45 hours
Film Type Humidity Cabinet test	60+ days

Health and Safety

Please refer to the relevant Trent Safety Data Sheet.

January 2025

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT. Trent Oil Lubricants Ltd. assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of Trent Oil Lubricants Ltd.

Trent Oil (Lubricants) Limited,
98A Lilac Grove, Beeston, Nottingham, NG9 1PF

Tel: 01159 279 166, Fax: 0115 9279 982

technical data