Trent Microcore QWDP

Medium Term Indoor Penetrating Fluid

Description

Trent Microcore QWDP is a light bodied solvent deposited oily film, temporary corrosion preventative suitable for Ferrous components, to give medium term inter-operational protection.

Trent Microcore QWDP is designed for fast and effective penetration, between two narrow parts.

Trent Microcore QWDP is designed to offer inter-operational protection when applied correctly to Ferrous components. This product is manufactured using hydrocarbon distillate and contains highly refined mineral oil of low aromatic content and specially selected corrosion inhibitors.

Trent Microcore QWDP will provide up to 12 months protection of parts (indoors) depending on storage conditions.

Application

Application can be made by brush, cold dip or spray.

The film is thin clear and oily, this can be removed if required by using an Alkaline Cleaner, Hydrocarbon Solvents or Vapour De-greaser. Where water displacement is of primary importance, the dip tank should be equipped with a bottom drain for removing accumulated water.

Benefits

- Medium-term indoor protection with a very light economical thin film.
- Contains specially selected corrosion inhibitors.
- Economical high surface coverage.
- Frees up seized parts.

Typical Inspection Data

Property	***Inspection Data***
Appearance	Dark Amber Fluid
Density at 15°C	0.81
Salt Spray Performance ASTM B117 (avg. hours)	15 hours
Humidity Cabinet test	60+ days

Health and Safety

Please refer to the relevant Trent Safety Data Sheet.

November 2025

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT. Trent Oil Lubricants Ltd. assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of Trent Oil Lubricants Ltd.

Trent Oil (Lubricants) Limited,
98A Lilac Grove, Beeston, Nottingham, NG9 1PF

Tel: 01159 279 166, Fax: 0115 9279 982

technical data