Trent Slideway Oil 68

Slideway Lubricant

Description

Trent Slideway Oil 68 is manufactured from the highest quality solvent refined base stocks and a special fourfold additive package.

Application

Trent Slideway Oil 68 is recommended for the lubrication of Slideways and for the prevention of stick, slip and chatter.

Trent Slideway Oil 68 is suitable for horizontal and vertical slides and ways due to the tacky adhesive additive pack used in the manufacture of this product.

Performance Profile

- Excellent extreme-pressure properties.
- Excellent anti-stick-slip properties promoting smooth table operation.
- Excellent demulsibility in the presence of soluble oils.
- Strong stickiness.
- Very low coefficient of friction.
- Anti-Oil mist properties.
- Outstanding anti-wear and anti-corrosion properties.

Typical Inspection Data

Property	***Method***	***Units***	***Inspection Data***
Viscosity Grade	-	-	68
Viscosity at 40°C	D 445	mm^2/s	68
Viscosity at 100°C	D 445	mm^2/s	8.9
Flash Point	D 92	°C	>200
Viscosity Index	D 2270	-	104
Specific Gravity @ 15.6°C		kg/m^3	0.884

Health and Safety

Please refer to the relevant Trent Safety Data Sheet.

January 2017

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT. Trent Oil Lubricants Ltd. assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of Trent Oil Lubricants Ltd.

Trent Oil (Lubricants) Limited,
98A Lilac Grove, Beeston, Nottingham, NG9 1PF

Tel: 01159 279 166, Fax: 0115 9279 982

technical data