Trent Spindle Oil 10

technical data

Description

Trent Spindle Oil 10 is manufactured from the highest quality solvent refined base stocks and special additives.

The formulation for Trent Spindle Oil 10 is based on the latest zinc free technology combining anti-wear performance with excellent filterability in both dry and wet conditions.

Trent Spindle Oil 10 formulated containing additives to enhance the resistance to oxidation (slugging), corrosion, foaming and improved lubricity.

Application

Trent Spindle Oil 10 is used in some critical hydraulic, circulation systems and air line oilers where the appropriate viscosity grade is required, use as received.

Typical Inspection Data

Property	***Method***	***Units***	***Inspection Data***
Viscosity Grade	-	-	10
Viscosity at 40°C	D 445	mm^2/s	10.3
Viscosity at 100°C	D 445	mm^2/s	2.5
Flash Point	D 92	°C	>125
Viscosity Index	D 2270	-	N/A
Specific Gravity @ 15.6°C		kg/m^3	0.830

Health and Safety

Please refer to the relevant Trent Safety Data Sheet.

January 2017

Prior to using this product, consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues. The information contained herein is based on data available to us and is believed to be accurate. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR TO BE IMPLIED, REGARDING THE ACCURACY OF THESE DATA. THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THE HAZARDS CONNECTED WITH THE USE OF THE PRODUCT. Trent Oil Lubricants Ltd. assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of Trent Oil Lubricants Ltd.

TRENT LUBRICANTS

Trent Oil (Lubricants) Limited,
98A Lilac Grove, Beeston, Nottingham, NG9 1PF

Tel: 01159 279 166, Fax: 0115 9279 982